

Laserliner

DigiLevel Pro 60 cm



Digital electronic level with spot laser as an optical extension for point-precise assessment of height and angle

- Measuring range pinpointing with laser circle display
- Measuring range pinpointing with laser circle display
- Short-term automatic saving of the last measurement value

TECHNICAL SPECIFICATIONS

VIAL ACCURACY	± 0.5 mm / m
ELECTRONIC MEASURING PRECISION	± 0.05° at 0° ... 1° ± 0.1° at 89° ... 90° ± 0.2° at 1° ... 89°
MEASUREMENT RANGE ANGLE MEASUREMENT	360°
DISPLAY ACCURACY 0° - 1°	2 decimal places
DISPLAY ACCURACY 1° - 90°	1 decimal place
LASER WAVELENGTH	650 nm
LASER CLASS	2 / < 1 mW (EN 60825-1:2014/AC:2017)
POWER SOURCE	2 x 1.5V LR03 (AAA)
OPERATING CONDITIONS	0°C ... 50°C, max. humidity 20 ... 85% rH, no condensation, max. working altitude 4000 m above sea level
STORAGE CONDITIONS	-10°C ... 60°C, max. humidity 80% rH, no condensation
DIMENSIONS (W X H X D)	610 mm x 60 mm x 30 mm
WEIGHT	800 g (incl. battery)