Laserliner



SmartCross-Laser GX Set 300 cm

Compact green cross-line laser with excellent visibility, 1/4" thread, TelePod 300 cm, and FlexClamp recycled material is used for sustainability

This cross-line laser projects a highly visible green laser cross, ideal for precise horizontal and vertical alignment of objects. It includes a manual slope feature to easily create inclines and a ¼" thread for mounting on the versatile FlexClamp, which also serves as a stable base. With FlexClamp, the laser can be quickly adjusted in position and height, then secured to the TelePod telescopic pole, suitable for room heights up to 3 meters. The TelePod provides a long spring travel in its tripod foot and is made of lightweight yet durable aluminum. The housing of the laser is made from a large proportion of recycled plastic and makes a valuable contribution to sustainability.

- Sustainable design: large proportion of the housing is made from recycled plastic
- Accurate horizontal and vertical alignment of objects
- Good visibility through green laser technology
- Easy alignment of slopes with manual tilt function
- The TelePod 300 cm telescopic pole precisely positions the laser for room heights up to 3 meters
- Sturdy aluminium version
- · Long spring distance on the stand foot
- The FlexClamp mount adjusts the laser's height and position with versatile, surface-safe mounting options
- · Integrated hand-held receiver mode for outdoor applications

Optional: Ran Artikel-Nr.: 033 max. 30 m	3.26E			H		max. 300 cm	n. cm		
Laser 515 nm	▲ ²	@ 3	RowerGreen	LEVEL	ERX READY	OPTION	1/4"	2x AA	SOFT
Item No.	036.736	E	GTIN	1 (EAN) 402	21563733	3910	SU 2		

TECHNICAL DATA						
Self-Levelling Range	± 4°					
Accuracy	± 0.3 mm / m					
Levelling	automatic					
Visibility (Typical)*	40 m					
Laser Wavelength	515 nm					
Laser Class	2 / < 1 mW (EN 60825-1:2014/ A11:2021 / EN 50689:2021)					
Power Supply	2 x 1.5V LR6 (AA)					
Operating Time	approx. 6 hours					
Operating Conditions	-10°C 50°C, max. humidity 80% rH, no condensation, max. working altitude 4000 m above sea level					
Storage Conditions	-20°C 70°C, max. humidity 85% rH					
Dimensions (W x H x D)	84 mm x 76 mm x 62 mm					
Weight	276 g (incl. battery)					

SCOPE OF DELIVERY



UMAREX GmbH & Co. KG • Laserliner • Gut Nierhof 2 • 59757 Arnsberg • Germany • Tel. +49 2932 9004-0 • info@laserliner.com • www.laserliner.com