## Laserliner

## SuperLine 2D


## Line laser for aligning work on all surfaces

The 2-axis line laser provides accurate horizontal and vertical alignment to the floor and walls. The 360° rotatable angle scale allows the device and the scale to be set independently of each other at any angle. The special pins and magnetic clamps ensure the device is securely attached onto surfaces such as finishing coats, carpets, wood, veneered surfaces and metal surfaces.

- Exact horizontal and vertical alignment of objects
- Easy adjustment of any angle and slope with 360° rotatable angle scale
- Special pins allow the device to be positioned on surfaces such as finishing coats, carpets, wood, veneered surfaces etc.
- Suitable for use on floors and walls
- Strong magnetic clamps for attaching to metal surfaces
- Easy-to-read, illuminated spirit-level

## TECHNICAL DATA

Vial Accuracy	± 1 mm / m
Accuracy	± 1 mm / m
Levelling	manual
Laser Wavelength	635 nm
Laser Class	2 / < 1 mW (EN 60825-1:2014/ A11:2021 / EN 50689:2021)
Power Supply	2 x 1.5V LR03 (AAA)
Operating Time	approx. 15 hours
Operating Conditions	0°C 50°C, max. humidity 80% rH, no condensation, max. working altitude 4000 m above sea level
Storage Conditions	-20°C 70°C, max. humidity 80% rH
Dimensions (W x H x D)	126 mm x 65 mm x 98 mm x (incl. holder)
Weight	188 g (incl. batteries)



SCOPE OF DELIVERY



Item No. 081.110A

GTIN (EAN) 4021563662579 SU 5

UMAREX GmbH & Co. KG • Laserliner • Gut Nierhof 2 • 59757 Arnsberg • Germany • Tel. +49 2932 9004-0 • info@laserliner.com • www.laserliner.com

