Laserliner



SmartCross-Laser


Automatic cross-line laser with additional slope **function**

This automatic cross-line laser is suitable for accurate levelling of horizontal and vertical surfaces and slopes, for example, when aligning studding, windows and doors. The laser lines can be switched individually and the device provides optical warning signals when it is outside its levelling range. The integrated hand-held receiver mode allows the laser lines to be detected by the optional laser receiver up to 30 metres away – ideal for all indoor and outdoor applications. A pendulum restraint provides excellent protection during transportation.



- · Additional slope function for aligning inclines
- · Individually switchable laser lines
- Time-saving automatic alignment
- Visual signals indicate when the device is outside its selflevelling range
- · With integrated handheld receiver mode
- Pendulum restraint for safe transport

IECHNICAL DATA	
Self-Levelling Range	± 5°
Accuracy	\pm 0.5 mm / m
Levelling	horizontal / vertical automatic
Visibility (Typical)*	10 m
Working Range with Hand Receiver	(depends on how the technology affects the difference in brightness) 40 m
Laser Wavelength	650 nm
Laser Class	2 / < 1 mW (EN 60825-1:2014/ A11:2021 / EN 50689:2021)
Power Supply	2 x 1.5V LR6 (AA)
Operating Time	approx. 15 hours
Operating Conditions	0°C 40°C, max. humidity 80% rH, no condensation, max. working altitude 4000 m above sea level
Storage Conditions	-10°C 70°C, max. humidity 80% rH
Dimensions (W x H x D)	75 mm x 85 mm x 55 mm
Weight	260 g (incl. batteries)














TECHNICAL DATA






















- AA --



GTIN (EAN) 4021563684533

SU 5