



## SuperCross-Laser 2GP Set 150cm



### Automatic cross-line laser with plumb function and hand-held receiver mode

This automatic cross-line laser is ideal for aligning horizontals, verticals and inclines. The green laser technology provides outstanding visibility. Additional plumb laser and reference beam for synchronous working on floor and ceiling. Optical signals warn the user when outside the levelling range. For long distances, the device has a built-in hand receiver mode. With the height-adjustable console, the laser can be fixed on the practical compact tripod, directly on the wall or on metallic surfaces. The pendulum locking is used for safe transport.

- Exact alignment of horizontal/vertical surfaces and slopes
- Good visibility through green laser technology
- Plumb function for synchronous working on floor and ceiling
- Time-saving automatic alignment
- Integrated hand-held receiver mode for outdoor applications
- Diverse range of mounting options on tripods, walls and metal surfaces
- Light and robust compact tripod
- Pendulum restraint for safe transport





\* Approx. 6 times brighter than a typical red laser with 630 - 660 nm



#### TECHNICAL DATA

<b>Self-Levelling Range</b>	± 4°
<b>Accuracy</b>	± 0.5 mm / m
<b>Levelling</b>	automatic
<b>Visibility (Typical)*</b>	40 m
<b>Working Range with Hand Receiver</b>	(depends on how the technology affects the difference in brightness) 40 m
<b>Laser Wavelength</b>	515 nm
<b>Laser Class</b>	2 / < 1 mW (EN 60825-1:2014/ A11:2021 / EN 50689:2021)
<b>Power Supply</b>	4 x 1.5V LR6 (AA)
<b>Operating Time</b>	approx. 6 hours
<b>Operating Conditions</b>	0°C ... 50°C, max. humidity 80% rH, no condensation, max. working altitude 4000 m above sea level
<b>Storage Conditions</b>	-10°C ... 70°C, max. humidity 80% rH
<b>Dimensions (W x H x D)</b>	124 mm x 119 mm x 66 mm
<b>Weight</b>	430 g (without accessories and batteries)



#### SCOPE OF DELIVERY



Item No. 081.192A      GTIN (EAN) 4021563715824      SU 2