





This cross-line laser produces two individually switchable, green laser lines — perfect for precise alignment of horizontal and vertical surfaces and slopes. The green laser technology provides excellent visibility. The device aligns itself automatically to save time and optical signals warn the user when it is outside its levelling range. The laser has a versatile clamping bracket for optimum use indoors and can be attached to surfaces without damaging them. A pendulum restraint provides excellent working Range with Hand Receiv



- Individually switchable laser lines
- · Additional slope function for aligning inclines
- GRX-Ready: integrated handheld receiver mode
- Out-Of-Level: Is indicated by optical signals when the unit is outside its self-levelling range
- Automatic Level: automatic alignment thanks to magnetically damped pendulum system
- Easy-to-adjust clamping bracket
- Versatile damage-free mounting options
- With 1/4" thread

IECHNICAL DATA	
Self-Levelling Range	± 5°
Accuracy	\pm 0.5 mm / m
Levelling	automatic
Visibility (Typical)*	40 m
Working Range with Hand Receiver	(depends on how the technology affects the difference in brightness) 60 m
Laser Wavelength	515 nm
Laser Class	2 / < 1 mW (EN 60825-1:2014/ A11:2021 / EN 50689:2021)
Power Supply	2 x 1.5V LR6 (AA)
Operating Time	approx. 3 hours
Operating Conditions	0°C 50°C, max. humidity 80% rH, no condensation, max. working altitude 4000 m above sea level
Storage Conditions	-10°C 70°C, max. humidity 80% rH
Dimensions (W x H x D)	77 mm x 90 mm x 60 mm
Weight	275 g (incl. batteries)
	** at max. 300 lux

























SCOPE OF DELIVERY



Item No. 081.336A

GTIN (EAN) 4021563698967

SU 4