



DampFinder Compact Plus



Material moisture measuring device

The DampFinder Compact Plus allows fast and accurate measurements of wood and building moisture. The measured values can be transferred through the Digital Connection interface to a mobile phone with the MeasureNote app.

- Fast and precise measurement of wood and building moisture
- Can be used to test many types of wood
- Extended material table with automatic conversion using the MeasureNote app
- Index function for optimum evaluation of various material categories
- Simple transfer of measured data through Digital Connection interface to mobile phone
- Effective testing of the measuring instrument using reference measurement through the protective cap
- Easy-to-read display



TECHNICAL DATA

Measured Variable	Moisture content of material (resistive) Ambient temperature
Mode	Wood (2 groups) Building materials (8 materials) Index
Measuring Range Ambient Temperature	-10°C ... 50°C
Accuracy Ambient Temperature	± 2°C
Measuring Range Wood	Wood group A: 5.6% ... 91.6% Wood group B: 7.3% ... 103.6%
Accuracy (Absolute) Wood	± 1% (5% ... 30%) ± 2% (<5% and >30%)
Measuring Range Building Materials	Anhydrite screed (AE, AFE): 0% ... 29.5% Concrete C12/15: 0.7% ... 3.3% Concrete C20/C25: 1.1% ... 3.9% Concrete C30/C37: 1.4% ... 3.7% Gypsum plaster: 0.1% ... 38% Limestone, bulk density 1.9: 0.8% ... 12.7% Cellular concrete (Hebel): 2.2% ... 171.2% Cement screed without additive: 1.0% ... 4.5%
Accuracy (Absolute)	± 0.15% (0% ... 10%)

SCOPE OF DELIVERY



Item No. 082.016A GTIN (EAN) 4021563705030 SU 5