



VideoScope One

Compact inspection camera for visual inspections of areas which are difficult to access


This compact video inspection system with waterproof camera head is suitable for easy visual inspection of hard-to-reach places in pipes, cavities, shafts, masonry and motor vehicles. Illumination with four high-performance LEDs provides clear pictures, even in extremely poor light. The image always remains clear on the monitor through rotation and mirroring. The high-contrast LC display also provides an optimum image, even in bright light.

- Easy problem localisation behind or in objects, walls, pipes, cavities
- Small camera head, ideal for places that are hard to reach
- Clear images even under the worst conditions
- Waterproof camera head and cable for use in sanitary areas
- Resistant to petrol and diesel
- Good object lighting due to 4 high-performance LEDs
- Image clearly discernible through rotation and mirroring
- Easy-to-read LC display



TECHNICAL DATA

| | |
|-------------------------------|--|
| Diameter Camera Head | 9 mm |
| Camera Resolution | 320 x 240 pixels |
| Field of View (FOV) | 53° |
| Depth of Focus (DOF) | 3 ... 7 cm |
| Screen Type | 2,7" Colour TFT |
| Display Resolution | 320 x 240 pixels |
| Length of Probe | 1.5 m |
| Illumination | 5 brightness levels |
| Digital Zoom | 2x digital zoom in 20% increments |
| Ports | RCA video output |
| Power Supply | 4 x 1.5V LR6 (AA) |
| Dimensions (W x H x D) | 100 mm x 200 mm x 130 mm x (without flexible tubing) |
| Weight | 510 g (incl. batteries) |



| LED LIGHT | ZOOM |
|-----------|-----------|
| 0 = 0% | 1x = 100% |
| 1 = 20% | 2x = 180° |
| 2 = 40% | 3x = 130% |
| 3 = 60% | 4x = 140% |
| 4 = 80% | 5x = 200% |
| 5 = 100% | |

SCOPE OF DELIVERY



1,5 m
VERSION
DOF 3...7 cm

