Laserliner

ActiveTester

Universal voltage tester for the entire electrical system of buildings

Direct and alternating voltages can be determined by using the 2-pole voltage tester. The device also provides information on the polarity. The ActiveTester can be used in many different situations; it identifies the most important nominal voltages and can be operated without batteries.

- Reliable and fast voltage tester with the most commonly used nominal voltages
- Practical, automatic test of AC and DC voltage
- Time-saving automatic range and function changeover
- · Efficient: one measuring instrument can be used for the entire building installation
- · Easy operation, no batteries required
- Sturdy, ergonomically designed housing

TECHNICAL DATA


Measured VariableDirect voltage / alternating voltageFeaturesautomatic measuring rangeAC VoltageRange / Resolution / Accuracy: 12, 24, 36, 50, 120, 230, 400V / 7 LEDs / -30% 0% of the reading Bandwidth: 50 / 60 HzDC VoltageRange / Resolution / Accuracy: 12, 24, 36, 50, 120, 230, 400V / 7 LEDs / -30% 0% of the readingProtection ClassIP 64Dimensions (W x H x D)60 mm x 245 mm x 25 mm		
AC Voltage Range / Resolution / Accuracy: 12, 24, 36, 50, 120, 230, 400V / 7 LEDs / -30% 0% of the reading Bandwidth: 50 / 60 Hz DC Voltage Range / Resolution / Accuracy: 12, 24, 36, 50, 120, 230, 400V / 7 LEDs / -30% 0% of the reading Protection Class IP 64 Dimensions (W 60 mm x 245 mm x 25 mm		Direct voltage / alternating voltage
12, 24, 36, 50, 120, 230, 400V / 7 LEDs / -30% 0% of the reading Bandwidth: 50 / 60 Hz DC Voltage Range / Resolution / Accuracy: 12, 24, 36, 50, 120, 230, 400V / 7 LEDs / -30% 0% of the reading Protection Class P64 Dimensions (W 60 mm x 245 mm x 25 mm	Features	automatic measuring range
12, 24, 36, 50, 120, 230, 400V / 7 LEDs / -30% 0% of the reading Protection Class IP 64 Dimensions (W 60 mm x 245 mm x 25 mm	AC Voltage	12, Ž4, 36, 50, 120, 230, 400V / 7 LEDs / -30% 0% of the reading Bandwidth:
Dimensions (W 60 mm x 245 mm x 25 mm	DC Voltage	12, 24, 36, 50, 120, 230, 400V / 7
• 60 mm ¥ 745 mm ¥ 75 mm	Protection Class IP 64	
	•	60 mm x 245 mm x 25 mm



CAT III 400V

SCOPE OF DELIVERY





SU 5