


This universal multimeter allows fast and accurate measurement of voltage, current and resistance. Integrity and polarity can be determined using the diode test function. The automatic continuity tester sends an acoustic signal to the user. No inconvenient cables have to be reconnected to switch between functions and ranges. The hold function allows the current measured value to be retained in the display - ideal for hard-toreach measuring points. The housing is largely made of recycled plastic, making a valuable contribution to sustainability.



- Accurate testing of voltage, current and resistance
- · Automatic continuity tester
- · Diode test function for determining integrity and polarity
- · Switch between function and range without reconnecting cables
- Easy-to-read display
- · Hold function for locking the current measured value on the

TECHNICAL DATA	
Measured Variable	Direct current / alternating current Direct voltage / alternating voltage Resistance
Features	automatic measuring range HOLD
AC Voltage	Range / Resolution / Accuracy*: 2.000V / 1 mV / ± (1.0% + 5) 20.00V / 10 mV / ± (1.0% + 5) 200.0V / 0.1V / ± (1.0% + 5) Bandwidth: 50 / 60 Hz
DC Voltage	Range / Resolution / Accuracy*: 200 mV / 0.1 mV / ± (0.8% + 5) 2.000V / 1 mV / ± (0.8% + 5) 20.00V / 10 mV / ± (0.8% + 5) 20.00V / 0.1V / ± (0.8% + 5) 250V / 0.1V / ± (1.0% + 5)
Dimensions (W x H x D)	56 mm x 113 mm x 23 mm













## SCOPE OF DELIVERY







